

General Features

- Non-spillable
- Sealed and Maintenance-Free Operation
- High Quality and High Reliability
- Exceptional Deep Discharge Recovery
- Low Self-discharge
- Long Service Life
- Tank-formed Plates
- Computer-aided Design and Manufacturing
- UL, CE Approved



Model	Nominal Voltage (V)	Rated Capacity (Ah)	Approx Dimension (mm)				Terminal type	Average Weight (kg)
			Length	Width	Height	Total Height		
			±1.5	±1	±2	±2		
NP12-5Ah	12	5	90	70	101	107	T1/T2	1.65
NP12-7Ah	12	7	151	65	94	100	T1/T2	2.1
NP12-7.2Ah	12	7.2						2.2
NP12-7.5Ah	12	7.5						2.2
NP12-8Ah	12	8						2.35
NP12-8.5Ah	12	8.5						2.5
NP12-9Ah	12	9						2.65
NP12-10Ah	12	10	151	98	95	101	T2/T1	3.1
NP12-12Ah	12	12					3.4	
NP12-15Ah	12	15	181	77	167	167	T3/T12	4.8
NP12-17Ah	12	17						5
NP12-18Ah	12	18						5.2
NP12-20Ah	12	20						5.5
NP12-24Ah	12	24	166	175	125	125	T4/T12	7.4
NP12-26Ah	12	26						7.9
NP12-28Ah	12	28						8.8
NP12-26Ah	12	26	166	175	125	125	T4/T12	8.05
NP12-24SAh	12	24	166	126	174	174/181	T14/T5	7.5
NP12-33Ah	12	33	195	130	155	167/180	T14/T6	10
NP12-38Ah	12	38	197	165	170	170	T14	11.8
NP12-40Ah	12	40						12.5
NP12-45Ah	12	45						13.8
NP12-50Ah	12	50	230	138	211	215	T14	16.2
NP12-55Ah	12	50	230	138	211	215	T14	17.3
NP12-60Ah	12	60	350	166	179	179	T14	19.3
NP12-65Ah	12	65						20.4
NP12-70Ah	12	70	260	169	211	215	T14	22.5
NP12-75Ah	12	75						23.5
NP12-80Ah	12	80						24.2
NP12-90Ah	12	90						306
NP12-100Ah	12	100	330	171	218	220	T19	29.5
NP12-120Ah	12	120	409	176	225	225	T16	34.8
NP12-150Ah	12	150	485	172	240	240	T16	41.8
NP12-160Ah	12	160	530	207	214	218	T16	49.5
NP12-180Ah	12	180	500	238	218	220	T12	53.5
NP12-200Ah	12	200	522	238	220	222	T19	59.5
NP12-250Ah	12	250	521	269	220	224	T16	71.5

Manufactured and Distributed by:
AUTOMATION SPECIALISTS AND POWER EXPONENTS, INC.



ASPEX Bldg., 159 Boni Avenue Brgy. Plainview, Mandaluyong City

Email: aspe@aspeinc.com.ph

Trunk line: (02) 997-0000 Fax: (02) 532-7228