

VALVE REGULATED LEAD ACID (VRLA) BATTERIES

KEY FEATURES

- ◆ Non - Spillable
- ◆ Sealed and Maintenance - Free Battery
- ◆ High Quality and High Reliability
- ◆ Absorbent Glass Matt (AGM)
- ◆ 13.5V to 13.8V Standby Voltage
- ◆ Computer - Aided Design and Manufacturing
- ◆ CE Approved



Model	Nominal Voltage	Rated Capacity	Approx. Dimension (mm)			Terminal type	Average Weight (kg)
			Length	Width	Height		
			±3	±3	±3		
ACU 12-7	12VDC	7AH	151	65	95	T1/T2	2.1
ACU12-9	12VDC	9AH	151	65	95	T1/T2	2.65
ACU12-12	12VDC	12AH	151	98	95	T1/T2	3.4
ACU12-18	12VDC	18AH	181	77	167	T3/T12	5.2
ACU12-26	12VDC	26AH	166	175	125	T4/T12	7.9
ACU12-40	12VDC	40AH	197	165	170	T14	12.5
ACU12-55	12VDC	50AH	230	138	211	T14	17.3
ACU12-65	12VDC	65AH	350	166	179	T14	20.4
ACU12-80	12VDC	80AH	260	169	211	T14	24.2
ACU12-90	12VDC	90AH	306	169	211	T14	27
ACU12-100	12VDC	100AH	330	171	214	T16	29.5
ACU12-120	12VDC	120AH	409	176	225	T16	34.8
ACU12-150	12VDC	150AH	485	172	240	T16	41.8
ACU12-200	12VDC	200AH	522	238	218	T18	59.5
ACU12-250	12VDC	250AH	521	269	220	T18	71.5



Exclusive Distributor



AUTOMATION SPECIALISTS AND POWER EXPONENTS, INC.

ASPEX Bldg., 159 Boni Avenue, Brgy. Plainview, Mandaluyong City

Trunk line: (02) 8997-0000 Fax: (02) 8532-7228

www.aspexinc.com.ph