

LINE INTERACTIVE UPS

KEY FEATURES

- ◆ SMT Technology
- ◆ Topology: Line Interactive UPS 1000VA
- ◆ Metal Case with Automatic Voltage Regulation (AVR) to correct voltage dips and surges to proper levels
- ◆ LED indication and audible alarm function
- ◆ Silence Setup and Smart battery management function
- ◆ AUTO Restart function when AC recovers
- ◆ Off charge and Cold Start function
- ◆ LCD Display is option



TECHNICAL SPECIFICATION

MODEL	AD1000
CAPACITY	1000VA / 600W
INPUT	
Nominal Voltage	230VAC
Voltage Range	170-280VAC
Network Frequency	50/60Hz +/- 5Hz (auto sensing)
Connection Type	NEMA 5-15P
OUTPUT	
Voltage	220/230/240VAC
Output Frequency	50/60Hz ±1 Hz
Transfer Time	4-6ms
Waveform	Stepped approximation to a sinewave
Connections/ Outlets	(4) Universal Receptacles
BATTERY	
Type	Maintenance-Free Sealed Lead-Acid Battery
Capacity	12V, 9.0AH
Recharge time	8 Hours
PROTECTION	
Full Protection	Over discharge, short circuit, overload, surge and lightning protection
Audible Alarms	Distinctive, low battery and overload warnings
Surge Energy Rating	156 Joules
INDICATORS	
Control Panel	LED status display with on line: on battery
ENVIRONMENT	
Humidity	0-90% RH @ 0-40°C (Non condensing)
Noise Level	Less than 40dB
IP Rating	IP 20
PRODUCT SIZE	
Dimensions (H x W x D)	15.0 cm x 10.0 cm x 33.0 cm
Weight	5.8 kg