

Key Features

- ◆ Non – Spillable
- ◆ Sealed and Maintenance-Free Battery
- ◆ High Quality and High Reliability
- ◆ Absorbent Glass Matt (AGM) Technology
- ◆ 13.5V to 13.8V Standby Voltage
- ◆ Computer - Aided Design and Manufacturing
- ◆ CE Approved



Technical Specifications

Model	Nominal Voltage	Rated Capacity	Approx. Dimension (mm)			Terminal type
			Length	Width	Height	
			±3	±3	±3	
NP12-7AH	12VDC	7AH	151	65	95	T1/T2
NP12-9AH	12VDC	9AH	151	65	95	T1/T2
NP12-12AH	12VDC	12AH	151	98	95	T1/T2
NP12-18AH	12VDC	18AH	181	77	167	T3/T12
NP12-26AH	12VDC	26AH	166	175	125	T4/T12
NP12-40AH	12VDC	40AH	197	165	170	T14
NP12-55AH	12VDC	50AH	230	138	211	T14
NP12-65AH	12VDC	65AH	350	166	179	T14
NP12-80AH	12VDC	80AH	260	169	211	T14
NP12-90AH	12VDC	90AH	306	169	211	T14
NP12-100AH	12VDC	100AH	330	171	214	T16
NP12-120AH	12VDC	120AH	409	176	225	T16
NP12-150AH	12VDC	150AH	485	172	240	T16
NP12-200AH	12VDC	200AH	522	238	218	T18
NP12-250AH	12VDC	250AH	521	269	220	T18



Exclusive Distributor



AUTOMATION SPECIALISTS AND POWER EXPONENTS, INC.

ASPEX Bldg., 159 Boni Avenue, Brgy. Plainview, Mandaluyong City

Trunk line: (02) 8997-0000 Fax: (02) 8532-7228

www.aspexinc.com.ph